

# Portable Projectors (MC Series)

Compact and light weight, MC Series projectors are easily portable and installed. The excellent price performance ratio makes these projectors especially suitable for classrooms and mid-sized meeting rooms.



## Specifications

Model	MC301X	MC331X	MC331W	MC371X	MC421X
Method	0.63 inch LCD				
Resolution**	1,024 × 768 (XGA)	1,024 × 768 (XGA)	1,280 × 800 (WXGA)	1,024 × 768 (XGA)	1,024 × 768 (XGA)
Lens	Manual zoom (×1.2) / Manual focus				
	F=2.1-2.25, f=19.109-22.936 mm Throw ratio = 70° @2.1m	F=2.1-2.25, f=19.109-22.936 mm Throw ratio = 70° @2.1m	F=1.6-1.76, f=19.158-23.018 mm Throw ratio = 70° @2.104m	F=1.6-1.76, f=19.158-23.018 mm Throw ratio = 70° @2.104m	F=1.6-1.76, f=19.158-23.018 mm Throw ratio = 70° @2.104m
Light source (lamp)	ECO mode off	225 W			
Lamp life**	ECO mode off	5,000 H			
	NormalECO	6,000 H			
	ECO mode	10,000 H			
Image size	30 to 300 inches				
Light output ** **	ECO mode off	3,000 ANSI lumens	3,300 ANSI lumens	3,300 ANSI lumens	4,200 ANSI lumens
	ECO mode	Approx. 80% at normal ECO mode			
Quietness (ECO mode off)	39 dB				
Contrast ratio (white / black)**	15,000:1 with dynamic contrast on				
Maximum resolution	Up to WUXGA (1920 × 1200)				
Synchronization range	Horizontal	15 kHz to 100 kHz (RGB: 24 kHz or over)			
	Vertical	50 Hz to 120 Hz			
Keystone correction	Horizontal: Manual ± Max 20 degrees / Vertical: Auto+Manual ± Max 30 degrees				
Input terminals	Computer	Mini D-sub 15 pin × 2 [Computer1 In , Computer2 In or Computer1 Out (Selectable)]			
	Video	RCA × 1			
	HDMI	HDMI × 2			
	Audio	Stereo mini jack × 1 D-sub 9 pin × 1			
Control terminals					
USB port	Type A for USB memory or Wireless LAN, Type B for PC control				
Built-in speaker	16 W monaural				
Usage environment	Operational temperature	5°C to 40°C, up to 80% humidity (no condensation)			
	Storage temperature	-10°C to 50°C, up to 80% humidity (no condensation)			
Power requirements	100 to 240 V AC, 50 Hz / 60 Hz				
Input current	1.6A				
Power consumption (typical)	ECO mode off	299W @200V			
	ECO mode	205W @200V			
	Standby (Normal)	0.5W or less @200V			
Dimensions (W × H × D)	335 × 99 × 250 mm (not including protrusions)				
Weight	2.9 kg				
Accessories	Power cord, remote control, batteries, signal cable, CD-ROM (User's manual), quick guide, important information, security sticker				

Contact me here :

**Kanchan Mishra**  
9502715576  
kanchanmishra@shibacomp.com

**NEC EXCLUSIVE**   
Multi-display management software

NaViSet Administrator-2 software is an all-in-one remote support solution that runs from a central location and provides monitoring, asset management and control functionality for a majority of NEC display devices and Windows computers. It is ideal for multi-device installations over larger infrastructures.

## NEC UNIQUE FEATURES

-  **15,000 : 1 CONTRAST**
-  **Built-in 16W speaker**
-  **USB plug-and-plug**
-  **Up to 10,000 hours lamp life**
-  **Auto & Direct power ON / OFF**

Shiba Comp Pvt Ltd, 520 Hemkunt Chambers, 89 Nehru Place, New Delhi 110019, India.  
Tel : +91 11 30822112 | Website : www.shibacomp.com